

XIS-100XDV



Artificial Intelligence (AI)

Enhanced Imaging[™] (EI)

Windows® Operating System with Intel® Core™ Processor

Dual 180kV Generators

Modular Design



PRODUCT DESCRIPTION

1988 **(**

RSTROPHYSICS

The XIS-100XDV[™] is a dual-view X-ray Inspection System (XIS) providing two distinct views for superior threat detection of baggage and large parcels at high-security locations. This dual-view system includes a side-mounted X-ray generator with a modular design allowing it to be disassembled and quickly reassembled on-site for ease of installation in confined spaces.

ABOUT ASTROPHYSICS

Since 2002, Astrophysics has led the industry in research and development, creating integrated solutions to advance the critical security missions of our customers and partners. Headquartered outside of Los Angeles, CA in the USA, Astrophysics has over 35,000 systems deployed in more than 150 countries, safeguarding critical infrastructure, aviation, and ports and border sites worldwide.

TOMORROW'S TECHNOLOGY FOR TODAY'S SECURITY™

XIS-100XDV^T

GENERAL SPECIFICATIONS

Tunnel Size: 100.3 cm x 100.1 cm $(W \times H)$ 39.5" x 39.4" Dimensions:1 303.1 cm x 176.6 cm x 197.8 cm (LxWxH) 119.4" x 69.5" x 77.9" Shipping Dimensions:1 345.4 cm x 194.3 cm x 224.8 cm (LxWxH) 136.0" x 76.5" x 88.5" 1435 kg (3165 lbs) Net Weight:1 Shipping Weight:1 1600 kg (3525 lbs) 23 cm/s (45 ft/min) Forward or Reverse Conveyor Speed: Conveyor Height: 76.8 cm (30.2") from Floor Conveyor Capacity: 220 kg (485 lbs) Evenly Distributed Load

X-RAY GENERATOR & IMAGE PERFORMANCE

Voltage:Dual 180kV, Operating at 165kVTube Current:Dual 1.2 mAWire Resolution:40 AWG Typical, 38 AWG StandardSteel Penetration:239 mm Typical, 37 mm StandardCooling:Sealed Di-Electric Oil Bath with Forced AirDuty Cycle:100%, No Warm-Up Procedure RequiredBeam Direction:Diagonally Upward, Horizontally Sideward

COMPUTER & VIDEO

Platform: Display Type: Display Resolution: Memory: Storage Capacity: Windows® 10 OS Dual 24" Flat Panel Monitors 1920 x 1200 8 GM RAM 256 GB SSD

0°C to 40°C / 32°F to 104°F

-20°C to 60°C / -4°F to 140°F

Up to 95% Non-Condensing

ENVIRONMENTAL

Operating Temperature: Storage Temperature: Humidity:

ELECTRICAL

System Power:	110VAC +/- 10% 50/60Hz, 20 Amp Max 220 VAC +/- 10% 50/60Hz, 15 Amp Max
Power Conditioner:	Uninterrupted Power Supply (UPS) (Computer Operation)

HEALTH & SAFETY

Compliant with USFDA Center for Devices and Radiation Health Standards for Cabinet X-ray Systems (21-CFR 1020.40) Typical radiation leakage is less than 0.1 mR/hr (Leakage less than 0.5 mR/hr permitted by U.S. Federal Standards)

FEATURES

STANDARD

3 & 6 Color Imaging Black & White Imaging Enhanced Imaging™ (EI) High Penetration Function Organic/Inorganic Imaging Pseudo Color Reverse Monochrome

Atomic Z-Number Measurement Geometric Image Distortion Correction Material Discrimination Real-Time Image Manipulation

Auto Image Archiving Image Review Save Image (RGB)

Baggage Counter

Image Annotation JPEG Conversion Print Image Capable

Multi-Tier Accessibility Network Ready Real-Time Self Diagnostics

9 Quadrant Zoom Continuous Scanning Continuous Zoom Up to 64x Vertical Zoom Panning

OPTIONAL

Barcode Scanning Density Alert Local Language Safe Passage® Computer Based Training Screener Assist Software Test Case Threat Image Projection (TIP) Software

Central Management System Integration Multiplexing

Conveyor Capacity Load Increase External USB Ports Variable Conveyor Speed

Custom Paint Entry/Exit Roller Tables Environmental Kit Sloped Conveyor

Footmat Operator Interlock Roller Bed

Radiation Meter Remote Workstation Configuration



3031 mm

119.4 in

ISO 9001 & ISO 14001 CERTIFIED



¹Weight and dimensions of the system may vary depending on customization. ²As tested on Astrophysics Inc. Test Piece.

³Optional Features may affect lead time, price, and weight of product. Please contact your Astrophysics Sales Representative for more information.

Due to continued product development, Astrophysics Inc. reserves the right to amend all technical specifications without prior notice. Contact sales@astrophysicsinc.com for the most updated brochures.

Astrophysics HQ +1.909.598.5488 Astrophysics – EMEA +961.9.832.500 Astrophysics – INDIA +91.11.41709990 Astrophysics – ASIA +63.2.812.0033 P/N 50-00-PB12-00 Rev.

2990

#000